

## Technical data

## DRD100-52S6

### Lifting data

Lifting capacity at load centre L4, rated - at max. lifting height	kg	10000 - 10000
Lifting capacity at load centre L5, rated - at max. lifting height	kg	9000 - 9000
Lifting speed, unloaded - at 70% of rated load	m/s	0,42 - 0,38
Lowering speed, unloaded - at rated load	m/s	0,4 - 0,4

### Driving data

Travelling speed forward, unloaded - at rated load	km/h	29 - 27
Travelling speed backward, unloaded - at rated load	km/h	29 - 27
Gradeability at 2 km/h, unloaded - at rated load	%	26 - 21
Max. gradeability, unloaded - at rated load	%	26 - 24
Drawbar pull	kN	118

Stability according to EN 1459

### Weight of truck

Service weight	kg	37400
Axle load front at load centre L4, unloaded - at rated load	kg	20400 - 36900
Axle load front at load centre L5, unloaded - at rated load	kg	22200 - 37200
Axle load front at driving position according to EN 1459 and rated load	kg	34100
Axle load rear at load centre L4, unloaded - at rated load	kg	17000 - 10500
Axle load rear at load centre L5, unloaded - at rated load	kg	15200 - 8200
Axle load rear at driving position according to EN 1459 and rated load	kg	13300

### Engine

Manufacturer - type designation		Volvo TWD 731 VE
Fuel - type of engine		Diesel - 4 stroke
Power according to ISO 3046 - at speed	kW-r/min	167 - 2200
Torque according to ISO 3046 - at speed	Nm-r/min	893 - 1300
Number of cylinders - compression		6 - 17.7:1
Alternator, type - power	W	AC - 1540
Starting battery, voltage - capacity	V-Ah	2x12 - 140
Fuel consumption, normal driving	l/h	12 - 14

### Transmission

Manufacturer - type designation		Clark - 13.7HR 32335
Clutch, type		Torque converter
Gearbox, type		Powershift
Number of gears, forward - reverse		3 - 3
Driving axle, type		Differential and hub reduction

### Wheels

Type, front - rear		Pneumatic
Dimension, front - rear		14.00x24 - 14.00x24, PR24 E3
Number of wheels, front - rear (* driven)		4* - 2
Pressure	MPa	1,0

### Steering and brake system

Steering system - manoeuvring		Servo assisted - Steering wheel
Driving brake system, type - affected wheels		Wet disc brakes - Drive wheel
Parking brake system, type - affected wheels		Spring brake - Drive wheel
Max. hydraulic pressure	MPa	21,2
Noise level according to DIN 45635 part 36, cabin - overhead guard	dB(A)	72
Fuel volume	l	400
Hydraulic oil volume	l	400
Overload protection		Electronical

### Dimensions

Beam angle, max.	°	$\alpha$	66°
Swivelling angle spreader, CW - CCW	°	$\beta$	195 - 105
Min. aisle for 90° stacking with 20' container	mm	A1	10900
Min. aisle for 90° stacking with 40' container	mm	A2	14100
Sideshift ±	mm	V1	±1000
Track (c-c), front - rear	mm	S	3285 - 2600

pdfMachine

**A pdf writer that produces quality PDF files with ease!**

Produce quality PDF files in seconds and preserve the integrity of your original documents. Compatible across nearly all Windows platforms, simply open the document you want to convert, click "print", select the "Broadgun pdfMachine printer" and that's it! Get yours now!

# Technical data

# DRD100-52S6

